

STEEL STRAPPING TOOL



SEAL-LESS JOINT HKE-L

A real all-rounder and the lightest tool in its class! HKE-L is an ergonomic design with minimal assembly and maintenance needs.

Technical Data

Kind of drive (tensioning)	Manually
Tension force	up to approx. 6,000 N
Kind of drive (sealing)	Manually
Dimensions	475 x 115 x 190 mm (L x W x H) 18.7 x 4.5 x 7.5" (L x W x H)
Weight	3.2 kg 7.1 lb

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband- up to approx. 900 N/mm ² tensile strength MEGABAND® up to approx. 1.100 N/mm ² tensile strength
Strap width	13, 16, 19 mm 1/2", 5/8", 3/4"
Strap thickness	0.40 - 0.60 mm 0.40 - 0.63 mm (for MEGABAND®) 0.016 - 0.024" 0.016 - 0.025 in (for MEGABAND®)
Kind of seal	Sealless-joint
Sealing strength	up to 75% of the strap breaking load

Minimum Bearing Area

Flat package	150 mm 5.9"
--------------	-------------

Application

Strapping of flat packages (e.g. palletized goods) for mobile use.



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Enclave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

