

# STEEL STRAPPING TOOL



## SEAL JOINT (SINGLE NOTCH) HV

The HV sealer is a purely manual seal joint with one notch. Light weight, minimalist design and robust technology for mobile applications. The complimentary counterpart of the HV sealer is the manual tensioner HR32, combined, they perform complete strapping.

### Technical Data

Kind of drive (sealing)	Manually
Dimensions	approx. 700 x 160 x 50 mm (L x W x H) HV/19 approx. 700 x 175 x 50 mm (L x W x H) HV/32 approx. 27.56 x 6.29 x 1.97" (L x W x H) HV/19 approx. 27.56 x 6.89 x 1.97" (L x W x H) HV/32
Weight	6.28 lb

### Strap/Joint

Type of strap	Steel strap
Strap	Automatenband
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm 0.031 - 0.039 in
Kind of seal	Seal-joint (single notch)



**Factory Address**  
Plot No. G28 & G29, General Park IP,  
Sultanpur Medical Devices Park,  
Telangana 502 319

**Corporate Address**  
Shantha Jubilee, Jubilee Enclave,  
HITEC City, Hyderabad,  
Telangana 500 081

**Contact** +91 93939 22442  
**E-mail** info@acmeirm.com  
**Website** www.mvsips.com

