

STEEL STRAPPING TOOL



SEAL JOINT (DOUBLE NOTCH) MAX

Designed for the extreme environmental conditions, MAX is a light weight yet powerful tool. The pneumatic motors develop an enormous tensioning force and is held consistently, thanks to a return stop after joining. MAX is designed for steel straps and closed by a seal with double notch.

Technical Data

Kind of drive (tensioning)	Pneumatic
Tension force	max. 8,000 N (adjustable)
Strap feeding speed	0.11 m/s 0.36 ft/s
Kind of drive (sealing)	Pneumatic
Seal (Type)	RSK 19 ; 25 ; 32
Dimensions	450 x 195 x 300 mm (L x W x H) 17.7 x 7.7 x 11.8" (L x W x H)
Weight	11,7 kg 25.8 lb
Air pressure	min. 5 bar flow pressure (for MEGABAND®) max. 6 bar flow pressure
Air consumption (tensioning)	11 NI / s
Air consumption (sealing)	6 NI / s
Cross-section	G 1/4 "
Handarm vibration	information currently not available
Noise level	76 dB (A)

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm (for Automatenband) 0.80 mm (for MEGABAND®) 0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)
Kind of seal	Seal-joint (double notch)
Sealing strength (depending on strap quality, strap dimensions)	up to approx. 75% of the strap breaking load

Application

Strapping of round and flat packages (e.g. sectional steel, bundles, pipes, coils, etc.) for stationary use.



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Enclave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

