

STEEL STRAPPING TOOL



SEAL JOINT (SINGLE NOTCH) MAXI-II

MAXI-II, the second generation compact, practical and handy tool for light applications in the steel industry is used for steel strapping with seal joint, however, where space is at a premium. Maxi-II is- Light weight, tubeless design and has excellent ergonomics & intuitive operability.

Technical Data

Kind of drive (tensioning)	Pneumatic
Tension force	max. 4,000 N (adjustable)
Kind of drive (sealing)	Pneumatic
Seal (Type)	RS 13 ; 16 ; 19
Strap feeding speed	0.11 m/s 0.36 ft/s
Dimensions	320 x 145 x 220 mm (L x W x H) 12.6 x 5.7 x 8.7" (L x W x H)
Weight	4.5 kg 9.9 lb
Air pressure	max. 4.0 bar Fließdruck (for 13 mm strap) max. 5.0 bar Fließdruck (for 16 mm strap) max. 6.0 bar Fließdruck (for 19 mm strap) max. 4.0 bar flow pressure (for 1/2 " strap) max. 5.0 bar flow pressure (for 5/8 " strap) max. 6.0 bar flow pressure (for 3/4 " strap)
Air consumption (during tensioning)	5 NI / s
Air consumption (during sealing)	5 NI / s
Cross-section	G 1/4"
Handarm vibration	information currently not available
Noise level	76 dB (A)

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	13, 16, 19 mm 1/2" ; 5/8" ; 3/4"
Strap thickness	0.40 - 0.60 mm (for Automatenband) 0.40 - 0.63 mm (for MEGABAND®) 0.016 - 0.024" (for Automatenband) 0.016 - 0.025" (for MEGABAND®)
Kind of seal	Seal-joint (single notch)
Sealing strength (depending on strap quality, strap dimensions)	up to approx. 50% of the strap breaking load

Application

Strapping of flat packages (e.g. palletized goods) for stationary use.



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Enclave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

