

STEEL STRAPPING TOOL



SEAL JOINT (DOUBLE NOTCH) PLC

A pure tensioner delivering highest force for extreme tensioning. It is used in conjunction with SCR or DCR sealers using crimp seals that allow controlled slipping of the strap in the seal, also serving as shock absorbers.

Technical Data

Kind of drive (tensioning)	Pneumatic
Tension force	20,000 N
Dimensions	400 x 130 x 140 mm (L x W x H) 15.7 x 5.1 x 5.5" (L x W x H)
Weight	8 kg 17.6 lb
Air pressure	max. 6 bar flow pressure
Air consumption (tensioning)	10 NI / s

Strap/Joint

Type of strap	Steel strap
Strap	MEGABAND® special
Strap width	32 mm 1 1/4"
Strap thickness	0.80 - 1.45 mm 0.031 - 0.057 in

Application

Lashing & Lifting: for load securing for rail and sea transport Strapping of e.g. steel coils, wood or cellulose, etc.



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Enclave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

