

STEEL STRAPPING TOOL



SEAL JOINT (DOUBLE NOTCH) PR 33

PR33, an ergonomic and effortless hand-held tool for heavy-duty strapping with seal joint used in combination with SPZ and DPZ pneumatic sealers. It is used for both, circular strapping and flat packages with easy maintenance and robust technology benefits!

Technical Data

Kind of drive (tensioning)	Pneumatic
Tension force	8,000 N
Dimensions	320 x 120 x 140 mm (L x W x H) 12.6 x 4.7 x 5.5" (L x W x H)
Weight	4.35 kg 9.6 lb
Air pressure	max. 6 bar flow pressure
Air consumption (tensioning)	0,6 m ³ / min. 21.18 ft ³ / min

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm 0.031 - 0.039"

Application

Strapping of packages and palletized goods with small contact surfaces.



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Enclave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

