

STEEL STRAPPING TOOL



SEAL JOINT (SINGLE NOTCH) SPZ

Simple steel strap sealer for circular and flat packages with intuitive handling and operation, user-friendly maintenance, robust pneumatic technology, ergonomic design. It is a single-notch seal joint. Match this with the TITAN PR33; if one notch is not enough, you can resort to the TITAN DPZ-L for double notch. Available in two variants: SPZ-E and SPZ-W meet the needs of a wide range of users with different grip angles.

Technical Data

Kind of drive (sealing)	Pneumatic
Seal (Type)	RSK, RSL
Dimensions	300 x 210 x 240 mm (L x W x H) 11.8 x 8.3 x 9.4" (L x W x H)
Weight	3.3 kg 7.3 lb
Air pressure	max. 6 bar flow pressure

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm (for Automatenband) 0.80 mm (for MEGABAND®) 0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)
Kind of seal	Seal-joint (single notch)

Application

Strapping of packages and palletized goods with small contact surfaces.



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Enclave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

